



## Relative Humidity and Temperature (RHS) Sensor

### AUTOMATIC CABIN HUMIDITY AND TEMPERATURE MONITORING

A Relative Humidity Sensor (RHS) makes vehicles more comfortable, saves fuel and promotes safer driving by automatically signaling the Climate Control System to optimize compressor usage and to prevent windshield fogging.

Sensata Technologies has been a leading global supplier of HVAC sensors for over 15 years.

Sensata Technologies offers a relative humidity sensor with an integrated temperature function. By utilizing innovative thin-film technology, Sensata sets the standard for accurate RH sensing with fast response time, and durability needed in automotive applications. The sensor outputs an accurate temperature and relative humidity measurement to the HVAC control module to optimize the efficiency of a vehicle's climate control system. This optimization results in improved customer comfort within the cabin, improved vehicle fuel economy, and anti-fogging strategies.

Features & Benefits	Benefits	Applications
Customized sensor output	Linear voltage output (0-5 V) 0-98% RH scale Temperature compensated Proven automotive EMC performance 15+ years of proven & reliable electronics	Safety • Anti-fogging HVAC system optimization
Thin film polymer technology	High accuracy Fast response time Long term stability Ability to recover quickly from condensation	• Tighter compressor control for lower emissions • Reduced heater core usage for Hybrid vehicles • Fuel economy Customer comfort
Robust custom packaging	Flexible packaging, easy integration Resistance to chemical & physical contaminants	• Cabin RH control (dry skin/eyes)

### Technical Specifications

Performance	Electrical
Operating Range ..... 0-98% RH	Supply Voltage ..... 5 ±0.25 V
Operating Temp ..... -30°C to 80°C	Current Draw ..... 10 mA max.
Initial Accuracy ..... ±4.0 RH*	Output Range ..... 0-5 V
Drift over 10 year life ..... ±4% RH*	Transfer function configurable to customer requirements
Response Time (tau) ..... <10 seconds	
Storage Temp ..... -40°C to 85°C	
*Stated accuracy quoted over -5°C to +30°C	
	<b>Temp Sensor</b>
	NTC Thermistor
	Accuracy ..... to ± .5°C
	Response Time ..... <30 seconds

# Relative Humidity and Temperature (RHS) Sensor

---

## Packaging Options

### Instrument Panel (IP) Mount



- Small package hidden in IP
- Flexible integration with interior design
- Optimally positioned in airflow return
- Air temp thermistor to calculate dew point for anti-fog application



The World Depends on Sensors and Controls

### Sensata Technologies

529 Pleasant Street, MS B41  
Attleboro, MA 02703-2964  
Phone 1-508-236-3800  
email: [auto-mktg@sensata.com](mailto:auto-mktg@sensata.com)  
[www.sensata.com](http://www.sensata.com)

Important Notice: Sensata Technologies (Sensata) reserves the right to make changes to or discontinue any product or service identified in this publication without notice. Sensata advises its customers to obtain the latest version of the relevant information to verify, before placing any orders, that the information being relied upon is current. Sensata assumes no responsibility for infringement of patents or rights of others based on Sensata applications assistance or product specifications since Sensata does not possess full access concerning the use or application of customers' products. Sensata also assumes no responsibility for customers' product designs.